

#### FRIB Remote Handling – Operations Experience and Future **Plans**

Michael Larmann, D. Cole, J. Morris, M. Mugerian, A. Stolz, J. Thelen, J. Wei

FRIB, Michigan State University, East Lansing, MI, USA

8<sup>th</sup> High Power Targetry Workshop, Riken, Japan





This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Nuclear Physics and used resources of the Facility for Rare Isotope Beams (FRIB) Operations, which is a DOE Office of Science User Facility under Award Number DE-SC0023633.

#### Outline

- FRIB Overview
- Equipment
- Beam Dump Maintenance
- Target Reconfiguration
- Current Operational Status
- Operational Experience
- Future Requirements



### **FRIB Overview**

- The Facility for Rare Isotope Beams
  - Heavy ion accelerator facility aiming to reach 400kW primary beams
  - Superconducting radio frequency continuous-wave heavy-ion linear accelerator
  - Accelerate all ions up to Uranium to energies above 200 MeV/u
  - Currently operating at 10kW

T. Maruta, 10:15-10:30am, Thur, Nov 9 J. Song, 10:15-10:30am, Fri, Nov.10





# **Target Hall Layout**

- Target hall allows for hybrid approach of both hands on and remote work to be completed
- Three remote workstations with shield windows and throughwall-manipulators
- Waste hatch to load liners into cask





#### **Target Hall Vacuum Vessels [1]**





### **Target Hall Vacuum Vessels [2]**

- Three main vessels
  - Target vessel
  - Beam dump vessel
  - Degrader vessel





### **Target Hall Vacuum Vessels [3]**

- Three main vessels
  - Target vessel
  - Beam dump vessel
  - Degrader vessel
- Two magnet types
  - Quadrupole
  - Dipole





### **Target Hall Vacuum Vessels [4]**

- Three main vessels
  - Target vessel
  - Beam dump vessel
  - Degrader vessel
- Two magnet types
  - Quadrupole
  - Dipole
- Three key devices
  - Target
  - Beam dump
  - Degrader





# **Target Hall Vacuum Vessels [5]**

- Three main vessels
  - Target vessel
  - Beam dump vessel
  - Degrader vessel
- Two magnet types
  - Quadrupole
  - Dipole
- Three key devices
  - Target
  - Beam dump
  - Degrader
- Shielding
  - Allows hands-on Target hall access





# Equipment [1]

#### Crane

- 20t capacity, PLC converted
- Fully automated 4 axis of motion
- Redundancy for recovery

#### Workstation window

- Lead window, 22"x28" viewing area
- 100lb capacity manipulators
- Ø100" table x 26' travel x 28,000lb cap. Lift

#### Fixturing and tooling

- DC nutrunner torque tools
- Specialized fixturing and tooling for each device
- Vision/Lighting
  - PTZ camera system
  - Lutron LED "Star" light system



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu



Window workstation target hall side

Window workstation operator side

### **Equipment** [2]



Remote handling control room

Target graphite disk change fixturing/tooling



#### **Target Hall Key Beamline Devices**

#### Target

- Rotating Ø12" graphite disk, max 5,000rpm
- Will absorb up to 100kW beam power
- Change graphite thickness for experiments at a frequency of up to weekly

#### Beam dump

- Currently using a static dump head
- 400kW operations requires rotating .5mm wall titanium drum, max 600rpm
- Will absorb up to 300kW primary beam
- Will perform maintenance yearly replacing drum, modules, and motors

#### Energy degrader

- Series of aluminum "wedge" shaped plates
- Will absorbs up to 6kW of beam power
- Change thickness and angle of wedge for experiments at a frequency of up to weekly



Facility for Rare Isotope Beams

U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA

640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu



Target assembly



Beam dump assembly

Degrader assembly

#### **Beam Dump Maintenance, Yearly**







#### **Target Maintenance, Weekly**





### **Target Power Ramp Up Path**





#### **Current Status**

- Successfully completed target changes since start of operations in May 2022
  - Total time from beam off to system ready for operations is currently 24hrs (assuming target is the only system scheduled for reconfiguration)
    - » Improved from 13 working days in September 2022



Torque tool removing shaft hub nut

Gripper removing old graphite disk



Torque tool removing old 20° static dump



- Completed two successful beam dump head changes
  - Total time from beam off to system ready for operations is 25 working days
    - » Improved from 29 working days in August 2022



#### **Current Radiation Levels**

- Measured radiation levels at the end of 5kW operations
  - Will ramp up to 400kW, 80x higher than current power
  - Remote handling will become more critical to reconfigure and maintain beamline devices



Target after start of operations through 5kW

20 mSv/h at exit aperture of heat exchanger door

400 mSv/h on dump head

6° static dump head after 1 year 5kW operation



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu

M. Larmann, November 2023 HPTW, Slide 17

# **Original Target Design**

 Modifications to target heat exchanger were found to be beneficial

- Original design included replacement of heat exchanger and bearing cartridge assembly during disk change
  - » Proved to be costly and time/resource consuming to fabricate heat exchangers
  - » Increases waste volume for disposal
  - » Requires separation of water cooling connections which need to be re-validated
  - » Cooling fins did not allow for disk removal



Heat exchanger assembly with disk and bearing cartridge



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu



Original multi-disk heat exchanger design

#### **Target Modifications**

- Modifications to a single disk target heat exchanger were made
  - Allows remote handling to remove graphite disk assembly only
    - » Cooling fins not required for single disk
    - » Changed downstream cover to hinged door
    - » Updated spindle shaft nut for remote interface
  - Remote operations proved successful
- Multi disk version required for higher power
  - Need to continue to remove just graphite disk
    - » Cooling fins will be required for multi-disk version
    - » Will need to separate heat exchanger remotely to allow for just graphite to be removed
    - » Consider adding workstation to change graphite disk configuration on hub remotely

Graphite Disk

Hinged Door



New single disk heat exchanger design



#### **Target Disk Tooling and Process [1]**





Target graphite disk change fixturing/tooling

Place target tooling on worktable located on lift



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu



Place target stand and assembly

#### **Target Disk Tooling and Process [2]**



Remove spindle nut



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu



M. Larmann, November 2023 HPTW, Slide 21

#### **Target Disk Tooling and Process [3]**



Open heat exchanger door and insert gripper



#### **Target Disk Tooling and Process [4]**





Clamp disk and remove from heat exchanger



#### **Target Disk Tooling and Process [5]**



Rotate fixture 180° and insert into waste staging container



#### **Target Disk Tooling and Process [6]**



Place and secure lid on staging container, remove, and place new disk on fixturing. Perform process in reverse to install new disk



#### New Scope, Target Bearing Replacement [1]

Developed capability to change just bearing cartridge • During 5kw operation temperature on spindle bearings was found to be higher than expected • To change bearings, the entire heat exchanger requires removal and disposal • Made minor part revisions to bearing housing and created 3d printed tooling to remotely change bearings



#### New Scope, Target Bearing Replacement [2]



tooling



#### **Additional Short Term Tooling [1]**

- High emissivity coating
  - Used 3d printed tooling to coat inside of target heat exchanger with high emissivity coating
  - Achieved coating with foam brush, prepped surface by wiping copper with Citric Acid and Acetone









#### **Additional Short Term Tooling [2]**

#### Inspection camera

• Utilize a digital microscope camera and adapted with stepper motors for zoom and focus to allow 10x-220x magnification inspection with manipulators remotely





#### **Future Requirements**

- 24hr target and degrader reconfiguration
  - Currently can change target disk or degrader ladder in 24hrs, unable to complete both
  - Will require 2<sup>nd</sup> complete target and degrader assemblies
  - Reconfiguration of devices will need to happen remotely during beam operations
- Proposed 24hr process
  - Turn off beam
  - Enter target hall, disconnect utilities
  - Close target hall and remotely remove target and degrader, place in work stand
  - Install pre-configured 2<sup>nd</sup> assemblies from canyon
  - Place removed assemblies from vessels into shielded canyon
  - Enter target hall and reconnect utilities
  - Continue Operations



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu



Degraders

# Thank You!



Facility for Rare Isotope Beams U.S. Department of Energy Office of Science | Michigan State University 640 South Shaw Lane • East Lansing, MI 48824, USA frib.msu.edu

M. Larmann, November 2023 HPTW, Slide 31